



SAFES

ROBUR IV - V



Burglary protection

The safes are tested in accordance with the European standard EN-1143-1 and certified by SBSC.

Fire protection

The safes in models: 500, 900, 1200 and 1500 are tested and classified in accordance with NT Fire 017 – 60P.

Description

The safes are constructed with a new barrier material in the door and body.

Weight and measurement

See overleaf

Locking

As standard the safe is provided with 2 changeable key locks type FAS/S&G 6890.

Available as option:

Combination lock type S&G 8550MP,

Electronic combination lock type Wittkopp.








Finish

Off white RAL 9010 with a matching control panel.

Fittings






See overleaf

Dimension in mms and kilos

Model	500	900	1200	1500	1800/2	1800/3
						
External measurements mm						
Height	695	1095	1395	1695	2015	2015
Width	690	690	690	690	920	1240
Depth *	730	730	730	730	870	870
Internal measurements mm						
Height	500	900	1200	1500	1820	1820
Width	500	500	500	500	730	1050
Depth	400	400	400	400	540	540
Weight kilos Grade IV	810	1070	1310	1550	2300	2800
Weight kilos Grade V	850	1110	1370	1630	2400	2950
Standard fittings	1 shelf	2 shelves	2 shelves	3 shelves	3 shelves	3 shelves

* **External depth**
+ 55 mm for handle

INTERIOR FITTINGS



Safe type	A	C	R
500	625	540	640
900	625	540	640
1200	625	540	640
1500	625	540	640
1800/2	855	770	870
1800/3	1175	1090	1190

Interior fittings	External height mm
A. Shelf	-
B. Lockable cupboard, small	155
C. Lockable cupboard, large	355
D. Sliding frame for A4/folio	-
E. Security cupboard	420
F. Lockable drawer, small	155
G. Lockable drawer, large	355

We reserve the right to alter the specification without prior notice.



Head office
Robur Safe AB
Lundbyvägen 8
SE-310 50 SLÖINGE
Phone: +46 346 260 260
Fax: +46 346 260 222

info@robursafe.com

www.robursafe.com